



	SPM 600	SPM 4000	SPM 6000
Volumenstrom (Polystyrol 0,5 mm Sieb) Flow rate (Styrene 0,5 mm screen) Débit (Polystyrène, orifice de 0,5 mm)	48 in ³ /s 800 cm ³ /s	122 in ³ /s 2000 cm ³ /s	122+ in ³ /s 2000+ cm ³ /s
Druckverlust ca. Loss of pressure approx. Pertes de pression, env.	73 lb / in ² 5 bar	73 lb / in ² 5 bar	73 lb / in ² 5 bar
Anzahl der Sieblöcher Number of screen holes Nombre d'orifices	528	1.062	2.088

	Bei Bestellung bitte angeben · Please specify on your order Indiquer pour toute commande										
	A		B		ØC	ØD	E	F _{max}	G	H	K
	min	max	min	max							
SPM 600	30	80	35	80	0,5	1,0	...	41	12,7	101,6	101,6
SPM 4000	30	64	35	80	0,5	1,0	...	41	12,7	177,6	114,3
SPM 6000	56	80	35	80	0,5	1,0	...	76	25,0	254,0	154,0

Bestellbeispiel · Order example · Exemple de commande

SPM 600 Maße A bis F beifügen · Enclose dimensions A to F · Inclure les dimensions A à F
Maschinendüse ist nicht enthalten · Machine nozzle is not included · La buse machine n'est pas comprise